






KT10433BBUOB



Features

- 0.43 inch digit height
- Low power requirement
- I.C. Compatible
- Easy assembly
- RoHs compliant
- Wide viewing angle
- End stack able
- Gray surface
- White segments
- Common Anode

CODE B



Code:BU Ultra Bright Blue (Gan)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage (Per dice)	Vf	If=20mA	3.0		3.6	V
Reverse Voltage (Per dice)	Vr	Ir=10uA		5		V
Luminous Intensty (Per dice)	Iv	If=20mA		100		mcd
Spectrum Width Of Half Value	△λ	If=20mA		22		nm
Wavelength	Dλ	If=20mA	465		470	nm
Peak Forward Current (Per dice) 1/10 Duty Cycle,0.1ms Pulse	Ifp	100				mA
Operating Temperature Range	Topr	- 35 ℃ to 85 ℃				
Storage Temperature Range	Tstg	- 35 ℃ to 85 ℃				
Solder Temperature 1.5mm below seating plane for 3 Seconds at 260 ℃						

Absolute Maximum Rating at Ta=25°C

Fig.1




Fig.2




Fig.3





Fig.4



Wave Soldering for Lead-Free Through-hole LED



Solder Temperature	260°C for 5 Seconds
--------------------	---------------------

Lead-free SMT process



Lead solder Temperature	235°C for 5 Seconds
-------------------------	---------------------

Notes: Recommend the wave temperature max. 235 °C.

Do not apply stress on the epoxy when temperature over 80 °C.

No more than once.