





Part No.	Colour	Wave Length	Lens Colour	Luninous In tensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL0250DCI	Red	700	Water Clear	4-6	1.7-2.4	20	140°
KTL0250CCI	Red	645		15-25	1.7-2.4	20	140°
KTL0250ACI-S	Red	630		60-100	1.7-2.4	20	140°
KTL0250ACI-U	Red	640		100-200	1.7-2.4	20	140°
KTL0250ACI-T	Red	623		200-400	1.7-2.4	20	140°
KTL0250KCI	Green	572	Water Clear	10-20	1.7-2.4	20	140°
KTL0250JCI	Green	572		20-50	1.7-2.4	20	140°
KTL0250JCI-S	Green	572		80-150	1.7-2.4	20	140°
KTL0250JCI-U	Green	572		200-300	1.7-2.4	20	140°
KTL0250ICI	Yellow	590	Water Clear	80-120	1.7-2.4	20	140°
KTL0250ICI-S	Yellow	590		120-200	1.7-2.4	20	140°
KTL0250ICI-U	Yellow	590		200-300	1.7-2.4	20	140°
KTL0250ICI-T	Yellow	590		300-400	1.7-2.4	20	140°
KTL0250FCI	Orange	610	Water Clear	40-80	1.7-2.4	20	140°
KTL0250FCI-S	Orange	610		120-200	1.7-2.4	20	140°
KTL0250FCI-U	Orange	610		200-300	1.7-2.4	20	140°
KTL0250BGCI	Blue-Green	510	Water Clear	300-400	3.0-3.6	20	140°
KTL0250BGCI-U	Blue-Green	510		400-800	3.0-3.6	20	140°
KTL0250BLCI	Blue	470	Water Clear	100-200	3.0-3.6	20	140°
KTL0250BHCI	Blue	470		200-300	3.0-3.6	20	140°
KTL0250BUCI	Blue	470		300-400	3.0-3.6	20	140°
KTL0250PGCI	Pure Green	525	Water Clear	500-800	3.0-3.6	20	140°
KTL0250PGCI-S	Pure Green	525		800-1200	3.0-3.6	20	140°
KTL0250PGCI-U	Pure Green	525		1200-1500	3.0-3.6	20	140°
KTL0250WCI	White	----	Water Clear	150-250	3.0-3.6	20	140°
KTL0250WHCI	White	----		250-400	3.0-3.6	20	140°
KTL0250WUCI	White	----		400-500	3.0-3.6	20	140°