



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL053DCI	Red	700	Water Clear	2-4	1.7-2.4	20	180°
KTL053CCI	Red	645		10-20	1.7-2.4	20	180°
KTL053ACI-S	Red	630		40-80	1.7-2.4	20	180°
KTL053ACI-U	Red	640		100-120	1.7-2.4	20	180°
KTL053ACI-T	Red	623		120-200	1.7-2.4	20	180°
KTL053KCI	Green	572	Water Clear	6-10	1.7-2.4	20	180°
KTL053JCI	Green	572		15-30	1.7-2.4	20	180°
KTL053JCI-S	Green	572		50-100	1.7-2.4	20	180°
KTL053JCI-U	Green	572		100-150	1.7-2.4	20	180°
KTL053ICI	Yellow	590	Water Clear	20-40	1.7-2.4	20	180°
KTL053ICI-S	Yellow	590		40-80	1.7-2.4	20	180°
KTL053ICI-U	Yellow	590		80-150	1.7-2.4	20	180°
KTL053ICI-T	Yellow	590		150-250	1.7-2.4	20	180°
KTL053FCI	Orange	610	Water Clear	10-20	1.7-2.4	20	180°
KTL053FCI-S	Orange	610		80-100	1.7-2.4	20	180°
KTL053FCI-U	Orange	610		100-150	1.7-2.4	20	180°
KTL053BGCI	Blue-Green	510	Water Clear	150-250	3.0-3.6	20	180°
KTL053BGCI-U	Blue-Green	510		300-400	3.0-3.6	20	180°
KTL053BLCI	Blue	470	Water Clear	60-80	3.0-3.6	20	180°
KTL053BHCI	Blue	470		80-120	3.0-3.6	20	180°
KTL053BUCI	Blue	470		120-200	3.0-3.6	20	180°
KTL053PGCI	Pure Green	525	Water Clear	150-250	3.0-3.6	20	180°
KTL053PGCI-S	Pure Green	525		250-350	3.0-3.6	20	180°
KTL053PGCI-U	Pure Green	525		350-450	3.0-3.6	20	180°
KTL053WCI	White	-----	Water Clear	100-150	3.0-3.6	20	180°
KTL053WHCI	White	-----		150-200	3.0-3.6	20	180°
KTL053WUCI	White	-----		200-250	3.0-3.6	20	180°