



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL05CDCI	Red	700	Water Clear	4-6	1.7-2.4	20	140°
KTL05CCCI	Red	645		15-25	1.7-2.4	20	140°
KTL05CACI-S	Red	630		60-100	1.7-2.4	20	140°
KTL05CACI-U	Red	640		100-200	1.7-2.4	20	140°
KTL05CACI-T	Red	623		200-400	1.7-2.4	20	140°
KTL05CKCI	Green	572	Water Clear	10-20	1.7-2.4	20	140°
KTL05CJCI	Green	572		20-50	1.7-2.4	20	140°
KTL05CJCI-S	Green	572		80-150	1.7-2.4	20	140°
KTL05CJCI-U	Green	572		200-300	1.7-2.4	20	140°
KTL05CICI	Yellow	590	Water Clear	80-120	1.7-2.4	20	140°
KTL05CICI-S	Yellow	590		120-200	1.7-2.4	20	140°
KTL05CICI-U	Yellow	590		200-300	1.7-2.4	20	140°
KTL05CICI-T	Yellow	590		300-400	1.7-2.4	20	140°
KTL05CFCI	Orange	610	Water Clear	40-80	1.7-2.4	20	140°
KTL05CFCI-S	Orange	610		120-200	1.7-2.4	20	140°
KTL05CFCI-U	Orange	610		200-300	1.7-2.4	20	140°
KTL05CBGCI	Blue-Green	510	Water Clear	300-400	3.0-3.6	20	140°
KTL05CBGCI-U	Blue-Green	510		400-800	3.0-3.6	20	140°
KTL05CBLCI	Blue	470	Water Clear	100-200	3.0-3.6	20	140°
KTL05CBHCI	Blue	470		200-300	3.0-3.6	20	140°
KTL05CBUCI	Blue	470		300-400	3.0-3.6	20	140°
KTL05CPGCI	Pure Green	525	Water Clear	500-800	3.0-3.6	20	140°
KTL05CPGCI-S	Pure Green	525		800-1200	3.0-3.6	20	140°
KTL05CPGCI-U	Pure Green	525		1200-1500	3.0-3.6	20	140°
KTL05CWCI	White	----	Water Clear	150-250	3.0-3.6	20	140°
KTL05CWHCI	White	----		250-400	3.0-3.6	20	140°
KTL05CWUCI	White	----		400-500	3.0-3.6	20	140°